

# Technical-Data-Sheet

---

No. 60, No. 62

## High voltage insulation tape

for insulation and padding



### Product description

Article name	No. 62
Material number	125589
Characteristics	Self-amalgamating
	Fuses to form a homogeneous, cavityfree compound within a short period of time
	Removable
	Durable
	Ozone-resistant
	Weatherproof
	Stabilized against UV rays
	No electrolytic corrosion
	Non tacky
	Extremely ductile
	Superior electrical properties
	Excellent adherence to a wide range of substances
	Superior physical properties
	Easy processing
Applications	Conductor insulation for polymeric insulated cables up to 69 kV
	Padding of cable insulation
	Sealing of casting moulds
	Repairing and connection of various insulating and cable materials e.g. PE, XLPE, EPR, PVC, butyl, neoprene

# Technical-Data-Sheet

---

## Technical data

Materials	EPR-Base
Length L	10 m
Width B	38 mm
Thickness	0.75 mm
Colours	black
Water absorption max	0.05 %
Dissipation factor (50 Hz)	5
Temperature range min	-40 °C
Temperature range max	100 °C
Elongation at break	900 %
Tensile strength at break	3 MPa
Specific volume resistivity	$10^{13} \Omega \text{ cm}$
Dielectric strength	42 kV/mm
Dielectric constant	2.8

# Technical-Data-Sheet

---

## Logistics data

Delivery scope	High voltage insulation tape
Country of origin	Great Britain
Customs tariff number	40051000

EAN-UPC	4010311059990			
Base quantity	1	1	24	1152
Base unit of measure	Piece	Piece	Piece	Piece
Alternate quantity	1	1	1	1
Alternative unit of measure	Piece	Bag1	Carton	Pal. OW
Length	112	112	375	1200
Width	112	112	250	800
Height	37	37	170	1100
Dimension unit	Millimetres	Millimetres	Millimetres	Millimetres
Volume	0.464	0.464	15.938	1056
Volume unit	Cubic decimetres	Cubic decimetres	Cubic decimetres	Cubic decimetres
Gross weight	0.317	0.317	7.908	383.384
Net weight	0.317	0.317	7.608	365.184
Weight unit	Kilogram	Kilogram	Kilogram	Kilogram